



i-GlooOil A1/B1 5W30 SL/CF

DESCRIPTION

i-GlooOil 5W30 high technology semi-synthetic engine oil formulated from refined base oil combined with a high level of synthetic components to provide good performance under the most difficult conditions.

BENEFITS

- Meets and surpasses the earlier specifications of Ford WSS-M2C-912-A1 and 913-A.
- Excellent low temperature stability for improved flow rates.
- Improved fuel efficiency.
- Semi-synthetic formulation.

APPLICATIONS

i-GlooOil A1/B1 5W-30 is suitable for normally aspirated and turbocharged petrol and diesel vehicles.

SPECIFICATIONS

i-GlooOil A1/B1 5W-30 meets the following performance specifications:

API	SL/CF
ACEA	A1/B1
FORD	M2C913-B
BMW	LL-01 FE
ILSC	GF-2

TYPICAL TEST DATA

Specific Gravity @ 15.6°C	0.875
Kinematic Viscosity @ 100°C (cSt)	11.40
Kinematic Viscosity @ 40°C (cSt)	69.02
Viscosity Index	159
Flash Point COC (°C)	225
Pour Point (°C)	-38
Total Base Number (mg KOH / g)	8.89



i-GlooOil A1/B1 5W30 SL/CF

