



MINERAL PREMIUM PETROL ENGINE OIL

i-GlooOil A3/B3 15W40 SM/CF

DESCRIPTION

i-GlooOil 15W40 SM is a multi-grade diesel engine oil manufactured from carefully selected base oils and the very latest additive technology. It meets many engine builder requirements and specifications. Superior dispersant additives help maintain engine cleanliness in the latest diesel engines and the latest detergent additives help reduce unwanted deposits in turbochargers and on pistons. i-GlooOil 15W-40 is suitable for normally aspirated and turbocharged highly stressed diesel engines in the passenger cars and heavy commercials, vans, plant, buses and industrial equipment.

BENEFITS

- High shear stability for stay in grade performance.
- Excellent high temperature stability.
- Improved bore polishing protection.
- Excellent anti wear performance for reduced engine wear.
- Ideal mixed fleet lubricant.
- Excellent sludge control for stop-go city motoring.

APPLICATIONS

i-GlooOil PREMIUM MINERAL 15W40 is suitable for normally aspirated and turbocharged highly stressed petrol engines and diesel engines in passenger cars and heavy commercials, vans, plant, buses and industrial equipment.

SPECIFICATIONS

API	SL/CH4
ACEA	A3/B3, A3/B4
MB	228.1, 229.1
MAN	271
VOLVO	VDS
VW	505.00
MACK	EO-L



MINERAL PREMIUM PETROL ENGINE OIL
i-GlooOil A3/B3 15W40 SM/CF

TYPICAL TEST DATA

Specific Gravity @ 15.6°C	0.889
Kinematic Viscosity @ 100°C (cSt)	20.88
Kinematic Viscosity @ 40°C (cSt)	189.03
Viscosity Index	131
Flash Point COC (°C)	235
Pour Point (°C)	-31
TBN (mg KOH / g)	10

