



i-GlooOil A3/B4 5W30 SM/CF

DESCRIPTION

i-GlooOil 0W-40 5W-30 is a high performance, fully synthetic multigrade petrol engine oil formulated to meet the long-life requirements demanded by GM and Opel. This grade of motor engine oil sets new standards with regard to engine cleanliness, reducing harmful emissions and thus damage to the environment.

i-GlooOil 5W-30 gasoline engine oil offers high levels of fuel economy and provides unrivalled protection for modern petrol and diesel engines.

BENEFITS

- Excellent high and low temperature performance.
- Exceptional long-term anti-wear characteristics.
- Very high standard of engine cleanliness.
- Long lasting dispersant performance and corrosion protection.
- Excellent sludge control for stop-go city motoring.
- High temperature protection against ring sticking.
- Reduced oil consumption and lower emissions.

APPLICATIONS

i-GlooOil 5W30 SM/CF A3/B4 motor oil, is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and small vans with extended oil drain intervals. This gasoline engine oil also contributes to the extension of the lifetime of particle filters. Because of its special composition it is possible to apply this product for the latest VW requirements.

i-GlooOil C3 5W30 MOTOR OIL A3/B3 API-SM/CF MEETS THE FOLLOWING PERFORMANCE SPECIFICATIONS:

ACEA	A3/B4
API	SM/CF
VW	504.00/507.00
BMW	LL-01, LL-98
MB	229.5
Porsche	C30



i-GlooOil A3/B4 5W30 SM/CF

TYPICAL TEST DATA

Density at 15°C kg/l	0.851
Viscosity -30 °C mPa.s	5950
Viscosity 40 °C mm ² /s	69.20
Viscosity 100 °C mm ² /s	12.00
Viscosity Index	171
Flash Point COC °C	230
Pour Point °C	-42
TBN mgKOH/g	6.7
Sulphate Ash %	0.67

