



i-GlooOil C2 SAE 0W30 SN/CF

DESCRIPTION

i-GlooOil C2 0W-30 SN/CF is the latest new generation fully synthetic low SAPS (sulphated ash, phosphorus and sulphur) multi-grade petrol engine oil formulated using the high quality base stocks and selected additive package. This motor oil has been developed primarily for modern Ford vehicles requiring the WSS-M2C950-A specification and recommended for applications requiring an ACEA C2, suitable for a variety of models from manufacturers including Jaguar Land Rover, Toyota, Honda and Kia.

BENEFITS

- Fuel saving technology.
- Compatibility with after treatment systems.
- Fully synthetic, long drain formulation.
- Very high standards of engine cleanliness.
- Exceptional anti-wear performance.
- Excellent high and low temperature performance.
- Tolerant of biodiesel contamination.

PACKAGING SIZE

1L, 4L, 5L, 20L, 208L, 1000L

APPLICATIONS and SPECIFICATIONS

A high quality all-round low SAPS engine oil suitable for use in a wide variety of modern petrol and light duty diesel engines. Recommended for use in Audi, VW, Mercedes-Benz, BMW, Toyota, Nissan where the listed specifications are required.

i-GlooOil C3 5W30 Motor oil API SN/CF API-SN meets the following performance specifications:	
API	SN/CF
ACEA	C2
Ford	WSS-M2C950-A
Jaguar Land Rover	STJLR.03.5007



i-GlooOil C2 SAE 0W30 SN/CF

TYPICAL TEST DATA

Density @ 15° C	0.841
Kinematic Viscosity @ 100°C (cSt)	9.3
Kinematic Viscosity @ 40°C (cSt)	43.7
Viscosity Index	203
Flash Point COC (° C)	220
Sulphated Ash (% wt)	0.79
Pour Point (°C)	-50

