



AUTOMATIC TRANSMISSION FLUID

GearOn FLUID 8HP

DESCRIPTION

GearOn AUTOMATIC TRANSMISSION FLUID 8HP is a synthetic ATF (Automatic Transmission Fluid), designed on the basis of high-quality base oils with approved additive and inhibition for making a perfect automatic transmission fluid for all 8 stroke automatic transmissions of ZF.

BENEFITS

- Very good lubricating capacity at low temperatures in winter.
- A high viscosity index.
- Finest oxidation stability.
- Works against corrosion and foam formation.
- Good thermal and oxidation stability.

APPLICATIONS

GearOn AUTOMATIC TRANSMISSION FLUID 8HP is suitable for use in automatic transmission of 8HP-Series transmission of ZF 8HP45, 8HP55, 6HP26, 8HP70, 8HP90, also for 6-stroke automatic 6HP-series - 6HP19X for AUDI Q7, 6HP19A, 6HP28AF.

SPECIFICATIONS

BMW	83222305397 (BIS 02.2013 83222152426) ATF L 12108
BMW	83222289720
VW/AUDI	G 060162 A1/A2/A6
VW	G 055 162
ZF	S671 090 312 , ZF TE-ML 11 9HP48
LAND ROVER	LR023288 UND LR023289
MOPAR	68218925AA ,68157995AB
FIAT	9.55550-AV5
ACURA	ATF TYPE 3.0
ACURA	08200-9016 A
HONDA	08200-9017
HONDA	ATF TYPE 3.1



AUTOMATIC TRANSMISSION FLUID

GearOn FLUID 8HP

TYPICAL TEST DATA

Density at 15	kg/m ³	844
Color		Green
Viscosity at 40°C	mm ² /s	26.4
Viscosity at 100°C	mm ² /s	5.6
Viscosity Index		160
Pourpoint	°C	-45
Flash Point	°C	226

