



AUTOMATIC TRANSMISSION FLUID

GearOn FLUID DEX VI

DESCRIPTION

GearOn AUTOMATIC TRANSMISSION FLUID DEX VI is a premium quality, fully synthetic automatic transmission fluid and is formulated primarily for applications requiring GM's Dexron VI specification.

GearOn AUTOMATIC TRANSMISSION FLUID DEX VI features many advantages over more traditional automatic transmission fluids such as improved shear stability, excellent wear control and extended fluid life.

BENEFITS

- Longer fluid life.
- Good low temperature performance.
- Backwards compatible to previous GM Dex specifications.
- Better frictional properties.
- Good wear protection.
- High film strength.
- Less foaming.

APPLICATIONS

Autotrans D VI is recommended for step type automatic transmissions and power steering units in cars, vans, trucks, buses and agricultural and industrial machines where the following specifications are required:

GM	Dexron VI, Dexron IIIH, IIIG, IID, TASA
JASO	1A
Allison	C-4
Caterpillar	TO-2
Mercedes-Benz	236.5
Voith	55.6335 (formerly G607)
Volvo	97340
ZF	TE-ML 09



AUTOMATIC TRANSMISSION FLUID

GearOn FLUID DEX VI

TYPICAL TEST DATA

Appearance	Red fluid
Density @ 15.6 °C	0.845
Kinematic Viscosity @ 100°C (cSt)	6.00
Brookfield Viscosity @ -40°C (cP)	12.030
Flash Point PMCC (°C)	190
Pour Point (°C)	-53

