

DESCRIPTION

i-GlooOil SAE40 is a mono grade petrol engine oil suitable for all petrol and naturally aspirated diesel engine oil. This petrol engine oil manufactured from selected base stock and good additive package to meet the manufacturer's recommendation.

BENEFITS

- Excellent high temperature stability.
- Improved bore polishing protection.
- Excellent anti wear performance for reduced engine wear.
- Excellent sludge control.

APPLICATIONS

i-GlooOil 40 may be used in a variety of turbocharged and naturally aspirated diesel engines where a monograde SAE 40 lubricant is specified. Main applications are earth movers, general plant equipment, large and small trucks, vans and taxis. SAE 40 may also be suitable for use in plant equipment hydraulic systems, transmissions and torque converters.

SPECIFICATIONS

API	SG/CF
Military	Mil-L-46152B/ Mil-L-2104D
Caterpillar	TO-2



i-GlooOil SAE 40 SF/CD

TYPICAL TEST DATA

Specific Gravity @ 15.6°C	0.890
Kinematic Viscosity @ 100°C (cSt)	14.8
Kinematic Viscosity @ 40°C (cSt)	141
Viscosity Index	105
Flash Point COC (°C)	224
Pour Point (°C)	-29
TBN (mg KOH/g)	9.20

