



i-GlooOil 15W40 SM/CH4 A3/B3

DESCRIPTION

i-GlooOil 15W-40 SM/CH4 is semi synthetic petrol engine oil which provide a high level of engine cleanliness and control the formation of high temperature and low temperature sludge. This motor oil has powerful anti-wear technology ensures maximum component life, together with protection from oxidation, rust and corrosion.

BENEFITS

- Excellent cold starting properties, even at low temperatures.
- A very stable and excellent viscosity behaviour and shear stability.
- Fuel savings under all operating conditions.
- Very good detergent and dispersing properties.
- Neutrality towards sealants.
- Low evaporation, thus low oil consumption.
- Extensive protection against wear, corrosion and foaming.
- Suitable for catalytic converters.
- Extended oil change intervals protect natural resources.

APPLICATIONS

i-GlooOil SL SAE 15W-40 is an engine oil for year-round use, and is ideal for all modern petrol and diesel car engines.

SPECIFICATIONS

i-GlooOil SM SAE 15W-40 can be used in engines with the specifications indicated.

i-GlooOil SL SAE 15W-40 meets the following performance specifications:

API	SM/CH4
ACEA	A3/B3, A3/B4
MB	228.1, 229.1
MAN	271
VOLVO	VDS
VW	505.00
MACK	EO-L
MTU	TYPE-1



i-GlooOil 15W40 SM/CH4 A3/B3

TYPICAL TEST DATA

Density at 15°C kg/m ³	0.872
Viscosity 100 °C mm ² /s	14.125
Viscosity Index	144
Pour Point °C	-3

