



i-GlooOil E7 SAE 15W40 CI4 SM

DESCRIPTION

i-GlooOil E7 SAE 15W40 CI4 SM high performance engine oil is a premium quality, heavy duty, multi grade semi synthetic in diesel engine or a mix of gasoline and diesel equipment. This lubricant is made by formulating with Group III base oils with an Advanced Detergent Additive System.

BENEFITS

- An excellent cold start property.
- A very good shear stability.
- An improved oxidation resistance.
- A very strong dispersion, therefore the deposits and sludge are restricted to a minimum.
- Excellent properties against wear, corrosion and foam.
- A lower oil consumption.

APPLICATIONS

i-GlooOil E7 SAE 15W40 CI4 SM engine oil is suitable for use in both on-highway and off-highway applications. This product complies with and exceeds the requirements of API CI-4.

SPECIFICATIONS

i-GlooOil E7 SAE 15W40 CI4 SM MEETS THE FOLLOWING PERFORMANCE SPECIFICATIONS:

API	CJ-4/SM
ACEA	E7/E9
Volvo	VDS-4
Renault	RLD-3
Mack	EO-O Premium Plus
MB	228.31
MAN	3575
CAT	ECF-2 ECF-3
Cummins	CES 20081
DDC	93K218
JASO	DH-2
Global	DHD-1
MTU	Type 2.1



i-GlooOil E7 SAE 15W40 CI4 SM

TYPICAL TEST DATA

Density @15°C kg/	0.874
Viscosity -20 °C mPa.s	6880
Viscosity 40 °C mm ² /s	108.70
Viscosity 100 °C mm ² /s	14.50
Viscosity Index	137
Flash Point COC °C	232
Pour Point °C	-36
Total Base Number mgKOH/g	7.8
Sulphate Ash %	0.92

