

i-GlooOil E9 SAE 15W40 CI4 / CH4

DESCRIPTION

i-GlooOil E9 SAE 15W40 CI4 / CH4 is a heavy-duty fuel-efficient multi-grade diesel engine oil, formulated using advanced Group II base oil and approved additive, for use in heavy-duty diesel engine applications. This diesel engine oil is developed to maximise the life of the particulate trap filter and may also be used in older engines.

BENEFITS

- Improved fuel efficiency and filterability.
- · Enhanced oxidation and thermal stability.
- High control over wear, rust and corrosion.
- · Good prevention of sludge and piston deposits.
- Extended drain capability.

APPLICATIONS

i-GlooOil E9 SAE 15W40 CI4 / CH4 is suitable for both Euro V and Euro VI engines as well as Tier 4 non-road diesel engines, where a low SAPS product of this quality is specified (sulphated ash, phosphorus and sulphur).

SPECIFICATIONS

ACEA	E9/E7
API	CI4/CH4
CUMMINS	CES 20086
FORD	171-F1
DETROIT	DIESEL DFS 93K222
MERCEDES BENZ	p228.31
CATERPILLAR	ECF-3
DEUTZ	DQC III-10-LA
MTU	Type 2



MINERAL PREMIUM PETROL ENGINE OIL

i-GlooOil E9 SAE 15W40 CI4 / CH4

TYPICAL TEST DATA

Density @ 15°C kg/m3 ASTM D1298	0.878
Kinematic Viscosity @ 40°C cSt ASTM D445	110.0
Kinematic Viscosity @ 100°C cSt ASTM D445	15.0
Viscosity Index - ASTM D2270	142
CCS @ -20°C cP ASTM D5293	6360
Pour Point °C ASTM D97	-36
Total Base Number (TBN)	15.0
Sulphated Ash %wt ASTM D874	1.0

