



i-GlooOil

HVI HYDRAULIC OIL AW ISO VG 68

DESCRIPTION

i-GlooOil HVI HYDRAULIC OIL AW ISO VG 68 is multi-grade hydraulic oil based on carefully selected solvent refined base oils under addition of additives to obtain the following properties:

BENEFITS

- A high and stable viscosity index.
- Excellent wear-preventing properties.
- A very good activity against corrosion.
- An excellent stability against oxidation.
- Very good demulsification properties.
- Very good deaerating and foam suppressing properties.
- Good compatibility with seals and gaskets made from synthetic material.
- A low pour-point.

APPLICATIONS

This hydraulic fluid is of tailormade quality for heavy duty hydraulic systems of earthmoving equipment and of permanent installations that have to work under high pressures over a wide temperature range. This fluid is not compatible in equipment with a silver lining.

SPECIFICATIONS

i-GlooOil HVI HYDRAULIC OIL AW ISO VG 68 meets the following performance specifications:

DIN	51524, 3 HVLP
FZG	12
Vickers	Vane Pump



i-GlooOil

HVI HYDRAULIC OIL AW ISO VG 68

TYPICAL TEST DATA

Density @15°C kg/	0.878
Viscosity 40 °C mm ² /s	68.00
Viscosity 100 °C mm ² /s	11.20
Viscosity Index	157
Flash Point COC °C	210
Pour Point °C	-35
Acid number mgKOH/g	0.40
Sulphate Ash %	0.06

