



i-GlooOil Marine Engine Oil SAE 15W-40

DESCRIPTION

i-GlooOil Marine Engine Oil SAE 15W-40 is a multi-grade marine oil for diesel engines for marine applications, is based on top-grade solvent-refined base oils and multifunctional additives.

BENEFITS

- A strong oxidation stability.
- A high and stable viscosity index.
- A high detergency and dispersion power.
- A good alkalinity, to neutralise the acid compounds which are produced during the combustion of a distillate diesel fuel .
- Effective in preventing from wear, corrosion and foam.
- A low pourpoint and good water separation power.

APPLICATIONS

Marine Engine Oil SAE 15W-40 marine oil is suitable as lubrication oil of high- and medium speed marine diesel engines with or without turbo-charging. This oil also can be used in shipboard gearboxes.

SPECIFICATIONS

i-GlooOil Marine Engine Oil SAE 15W-40 meets the following performance specifications:

API		CF
MIL		L-2104C



i-GlooOil Marine Engine Oil SAE 15W-40

TYPICAL TEST DATA

Density at 15°C kg/l	0.885
Viscosity -20 °C mm ² /s	6200
Viscosity 40 °C mm ² /s	109.40
Viscosity 100 °C mm ² /s	14.30
Viscosity Index	133
Flash Point COC °C	226
Pour Point °C	-32
Total Base Number mgKOH/g	16
Sulphate Ash %	1.67

